



Flexyfix All Floors Adhesive

Issued: 20/06/2022

Page 1 of 1

Technical Data:

Base	Acrylic
Consistency	Paste
Curing System	Physical drying
Open Time*	Max. 30 min.
Drying time	Approx. 12 Hours
Specific Gravity (DIN 53479)	Approx. 1,44 g/cm ³
Temperature Resistance (cured)	-20°C to +80°C
Solid content	Approx. 76 %
Consumption	Approx. 250-600 g/m ² ; depending on subfloor and used notched trowel
Tools	Trowel A2, for (Cushion) Vinyl Trowel A3, for carpet with a latex backing, PVC flooring Trowel B1/B2, for carpet with sackcloth, actionback, polystyrene or felt backing, fibrebonded and linoleum

* This varies according to ambient conditions such as temperature, humidity, substrate etc.

Product:

Flexyfix All Floors adhesive is a single component dispersion adhesive containing synthetic resins for indoor use.

Characteristics:

- Easy to apply
- Professional quality
- Long open time
- High final bond strength
- Excellent wet-grab

Applications:

For bonding all kinds of floor covering such as carpet with foam backing, synthetic Jute (hessian) as well as vinyl, PVC and linoleum to most substrates.

Surfaces:

Type: porous subfloors such as concrete or wood.

State of surface: Flexyfix All Floors adhesive should be applied to an even, dry, clean and smooth substrate, which is also free from irregularities and cracks. Levelling compound should be applied where irregularities occur. Residues of old adhesives may affect the bond and must be removed mechanically.

Preliminary treatment: none - We recommend a preliminary compatibility test.

Applying the adhesive:

Method: Apply the adhesive by means of a notched trowel (B1 for vinyl/PVC and B2 for floor covering with jute or synthetic backing) to the substrate.

Do not apply more adhesive to the subfloor than can be covered with floor covering within 20 - 30 mins. Place the floor covering onto the adhesive and press down firmly. A heavy roller is ideal for this purpose.

Application temperature: +5°C to +35°C

Cleaning: Uncured adhesive may be removed from tools and materials with water. Cured adhesive must be removed mechanically.

Packaging:

Colour: white-tan

Packaging: 15kg

Shelf life:

24 months in unopened original packaging in a dry storage place at temperatures between +5°C and +25°. Do not expose to frost.

Health- and safety recommendations:

Apply the usual industrial hygiene precautions. Wear protective gloves. Consult the label for more information.



Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.